


Default data transmit format

Code	Message Format
EAN 13	D1 D2 D3 D4 D5 D6 D7 D8 D9 D10 D11 D12 D13
EAN 8	D1 D2 D3 D4 D5 D6 D7 D8
UPCA	D1 D2 D3 D4 D5 D6 D7 D8 D9 D10 D11 D12
UPCE	D1 D2 D3 D4 D5 D6 D7
Code 128	D1 - Dx
EAN 128]C1 D1 - Dx
Code 39	D1 - Dx
Code 32	D1 - Dx
Codabar	D1 - Dx
Interleaved 2/ 5	D1 - Dx

Please note that EAN/ UPC codes with AddOn are transmitted without a separator.


GENERAL

ENTER/ EXIT PROGRAMMING MODE




10

EXIT PROGRAMMING MODE WITHOUT UPDATE




11

RETURN TO FACTORY DEFAULT SETTINGS



12

RETURN TO CUSTOM DEFAULT SETTINGS




13

SCANNER FUNCTIONALITY


GOOD READ BUZZER SETTINGS

GOOD READ BUZZER FREQUENCY



GOOD READ BUZZER VOLUME


18



19


SLEEP MODE

SLEEP MODE DISABLE




ENTER SLEEP MODE AFTER 10 MINUTES

22




ENTER SLEEP MODE AFTER 30 MINUTES (DEFAULT)

23



ENTER SLEEP MODE AFTER 60 MINUTES


24



25


SAME CODE DELAY SETTINGS

SAME CODE DELAY 50mSec




SAME CODE DELAY 100mSec

28




SAME CODE DELAY 200mSec

29




SAME CODE DELAY 300mSec

30




SAME CODE DELAY 600mSec (DEFAULT)

31



SAME CODE DELAY 1000mSec

32




33

COMMUNICATION PARAMETERS


RS232 COMMUNICATION

BAUDRATE 300




BAUDRATE 600

38




BAUDRATE 1200

39




BAUDRATE 2400

40




BAUDRATE 4800

41




BAUDRATE 9600 (DEFAULT)

42




BAUDRATE 19200

43




BAUDRATE 38400

44




PARITY NONE (DEFAULT)

45




PARITY EVEN

46




PARITY ODD

47




PARITY MARK

48




PARITY SPACE

49




7 DATABITS

50




8 DATABITS (DEFAULT)

51




1 STOP BIT

52




2 STOP BITS (DEFAULT)

53




RTS/ CTS ON

54




RTS/ CTS OFF (DEFAULT)

55




RS232 PRESET 1

56




RS232 PRESET 2

57




RS232 PRESET 3

58




RS232 PRESET 4

59




RS232 PRESET 5

60



RS232 PRESET 6


61



62


OCIA COMMUNICATION

OCIA BYTE FORMAT DTS (DEFAULT)




OCIA BYTE FORMAT NCR SHORT

64




OCIA BYTE FORMAT NCR LONG

65




OCIA PRESET 1

66




OCIA PRESET 2

67




OCIA PRESET 3

68



OCIA PRESET 4

69



70

IBM RS485 COMMUNICATION